

RIGID ALUMINUM INFLATABLE VESSEL

RAIV



When the demands include exceptional longevity, a soft ride, a stable platform and one of the most seaworthy hulls for its size, the RAIV is precisely the working vessel you need. The name stands for Rigid Aluminum Inflatable Vessel, and the hull sponsons include up to a seven-compartment polyurethane tube assembly.



800-413-6351
commercialsales@northriverboats.com
NorthRiverBoats.com
AlmarBoats.com

 **NORTH RIVER**
Boats
TRUSTED-TIMELESS-TOUGH

 **Almar**
ALUMINUM BOATS

RAIV

MILITARY • HARBOR SECURITY • PATROL • SEARCH & RESCUE • FIRE • PILOT •
VESSEL ASSIST • SURVEY • DIVE OPS • USCG SUB-T

LENGTH		BEAM		TUBE DIAMETER		DEADRISE	CENTER CONSOLE	T TOP	WHEEL HOUSE	WALK AROUND	CUDDY CABIN	VALOR CABIN
20'	6.1 m	8'6"	2.6 m	20"	0.51 m	20°	X	X	N/A	N/A	N/A	N/A
21'	6.4 m	8'6"	2.6 m	20"	0.51 m	20°	X	X	N/A	N/A	N/A	N/A
22'	6.7 m	8'6"	2.6 m	20"	0.51 m	20°	X	X	N/A	N/A	N/A	N/A
23'	7 m	8'6"	2.6 m	20"	0.51 m	20°	X	X	N/A	N/A	N/A	N/A
24'	7.3 m	8'6"	2.6 m	20"	0.51 m	20°	X	X	N/A	N/A	N/A	N/A
20'	6.1 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
21'	6.4 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
22'	6.7 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
23'	7.0 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
24'	7.3 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
25'	7.6 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
26'	7.9 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
27'	8.2 m	9'	2.7 m	22"	0.56 m	20°	X	X	N/A	N/A	N/A	N/A
25'	7.6 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
26'	7.9 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
27'	8.2 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
28'	8.5 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
29'	8.8 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
30'	9.1 m	10'	3.0 m	24"	0.61 m	24°	X	X	X	N/A	X	N/A
Note: Cuddy Cabin (25' - 26') 6' Fwd Leaning / (26' - 29') 8' Fwd Leaning / (30') 10' Fwd Leaning												
28'	8.5 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
29'	8.8 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
30'	9.1 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
31'	9.4 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
32'	9.8 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
33'	10.1 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
34'	10.4 m	12'	3.7 m	28"	0.71 m	24°	X	X	X	X	X	X
Note: Walk Around Cabin (28' - 34') 8.5' Cabin; Cuddy Cabin (28' - 29') 8' Fwd Leaning / (30' - 34') 10' Fwd Leaning												
31'	9.4 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
32'	9.8 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
33'	10.1 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
34'	10.4 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
35'	10.7 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
36'	10.97 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
37'	11.3 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
38'	11.6 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
39'	11.9 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
40'	12.2 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
41'	12.5 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
42'	12.8 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
43'	13.1 m	13'	3.96 m	28"	0.71 m	24°	X	X	X	X	X	X
Note: Walk Around Cabin (31' - 43') 8.5' Cabin; Cuddy Cabin (31' - 36') 10' Fwd Leaning / (37' - 43') 12' Fwd Leaning												